

1330 82-Column Flatbed Dot Matrix Printer



Tally Dascom's 1330 flatbed serial dot matrix printer, is a 24-pin, 82-column printer with USB interface as standard. The 1330 is ideal for front office applications in retail outlets, travel agents, train stations, banks and doctor's surgeries where space is limited.

The 1330 is equipped with a linear encoder sensor to position the print head with high accuracy and intellectually detect and correct any misplaced carriage, which ensures good printing quality and significantly reduces the chances of errors in printing.

Highlights at a glance

- Advanced 24-pin, flatbed printer
- Up to 450 CPS speed
- Ideal for front and back office application
- Up to 7-ply copy capability
- 9 mil characters long life ribbon
- 8.2 inches print width, supports A3 portrait
- Intelligent print position tracking sensor
- Wide range of optional interfaces
- Large 256 KB buffer size

With high quality output, an easy to use control panel and the option to use pre-cut or tractor fed paper, the 1330 is ideal for counter-top printing applications such as cheques, tickets, receipts, forms and multi-part documents.

Using the long life ribbon option, the 1330 requires fewer ribbon changes, less downtime and lower running costs. With print speeds of up to 450 characters per second (cps) and flexible media handling, it keeps transactions smooth and the user happy.

The 1330 is a reliable and easy to use printer, with low running costs and a small footprint.

Available Configurations:

- 1330 Standard Product
- 1330 Standard Product + optional interface

1330

Print Speed	450 cps (Fastest Mode); 300 cps (Draft, 10 CPI), 200 cps (NLQ, 10CPI), 100 cps (LQ, 10 CPI)
Print Method	24-pin impact dot matrix
Resolution	Up to 360 x 360 dpi
Character Pitch	10, 12, 15, 16.6, 17.1, 20, 24 cpi, Proportional Spacing
Line Spacing	1/6 inch, programmable in 1/360 inch increments
Printhead life	400 Million Strokes per pin
Memory Buffer	Up to 256 KB
Standard Connectivity	USB 2.0; Optional: Parallel/Serial/Ethernet/WIFI/Bluetooth
Standard Emulation	Epson (ESC P/2), IBM PPDS
Fonts	HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Orator, Gothic, Script, Souvenir, OCR-A/B Barcodes: EAN-13, EAN-8, Interleaved 2 of 5, UPC-A, UPC-E, Code 39, Code 128, Postnet
Character Sets	58 types supported
Ribbon Life	9 million characters
Standard Paper Handling	Friction and push tractor
Number of Copies	Up to 1 Original + 6 copies
Paper Type	Cut sheet and continuous forms
Paper Weight	52 - 120 gsm
Paper Size	55 - 297 mm
Physical Weight	4.2 kg
Physical Size	395 x 320 x 205 mm (W x D x H)
Power Voltage & Frequency	AC 100-120 V / 200-240 V; 50-60 Hz
Power Consumption	Average: 34W, Sleep: 1.4W; Energy Star 2.0 compliant
MTBF	12,000 hours
MVBF	24 Mil lines
Drivers	Windows 2000/XP/Vista/7/8/8.1/10 and Server 2003/2008/2012R2/2014
Utility	Tally Dascom Printer Config Tool
Temperature	5° C to 35° C
Humidity	10% to 95% (non-condensing)
Acoustic	< 53 dB(A) (ISO 7779)
Standard Warranty	One year

DASCOM AP Pte Ltd

21 Bukit Batok Crescent
#29-81 WCEGA Tower
Singapore 658065
TEL: +65 6760 8833
FAX: +65 67601066
Email: sales@dascom.com.sg
Website: www.dascom.com.sg

SERIAL MATRIX PRINTERS

MOBILE PRINTERS

FLATBED PRINTERS

THERMAL PRINTERS